

COLOURS

To overcome any minor shade variations inherent in the production of natural clay products, we recommend that tiles are mixed from at least 3 pallets on site.



SLATE

The colours shown here are only as accurate as allowed for by the printing process. Product samples are available on request.







This product was manufactured by an organisation certified compliant, by AFNOR Certification, with the following benchmarks: ISO 9001 for quality, ISO 14001 for the environment, and ISO 50001 for energy. All EDILIANS roof tiles comply with the requirements of the NF EN 1304 standard. Only tile models identified by the NF, NFM, or NFFP logo are compliant with the requirements of the NF063 Clay Roof Tiles certification. The characteristics certified by the NF Clay Roof Tiles specification are appearance, geometric characteristics, resistance to breakage by bending, Class I waterproofing, resistance to freezing in accordance with NF EN 539-2, resistance to "mountain climate" freezing (for models bearing the NFM logo only), and suitability for use on low-pitch roofing (for models bearing the NF FP logo only). www.marque-nf.com

BEAUVOISE GRAPHITE Huguenot

CLAY SLATE

Small Format Interlocking Clay Slate



ation on our website, by @ 2024 Easycom

This document is not contractual and may be changed at any time (see the latest inform 554 224, registered office 65, chemin du Moulin Carron, 69570 Dardilly, France. Created

BEAUVOISE GRAPHITE Huguenot

Small Format Interlocking Clay Slate

Technical data

Quantity per pallet:

480 tiles

Coverage at 245mm gauge:

20.5 tiles per m²

Nominal batten gauge*:

245mm

Overall length:

322mm

Overall width:

Cover width:

200mm

Headlap: 77mm

Weight per tile:

1.9kg

Weight per m² at maximum gauge:

39.0kg

Minimum roof pitch:

Batten coverage m²:

4.08m

Batten sizes:

38 x 25mm for rafter centres up to 450mm

50 x 25mm for rafter centres up to 600mm

Tile nail:

50 x 3.35mm aluminium clout head

* Always check each batch of tiles delivered to site to determine the actual gauge, which may vary slightly due to drying and fi ring shrinkage during the manufacturing process



CLAY SLATE

Small Format Interlocking Clay Slate

The Edilians Huguenot BEAUVOISE GRAPHITE clay slate provides an exciting natural clay option, offering a durable high-performance roof covering saving up to 30% on material costs alone when compared with natural slate. Reduced labour costs will also increase this differential considerably due to no on-site grading requirements. Each tile has two nail holes for ease of fixing when cutting or installing around hip and valley areas.

FEATURES

- Up to a 30% saving against natural slate
- · Varied all round chamfered slim line edge
- Authentic modular slate size
- Minimum 22.5° roof pitch
- Low overall weight of 39kg per m²
- Insurance-backed 30-year durability quarantee

ACCESSORIES AND FITTINGS

An extensive range of accessories covering all roofing needs

Verge



Ref. 312.01





Ref. 312.85






Ref. 312.80

Angular ridge







Ref. 859

Ornamental ridge




Half round interlocking ridge



Ref. 717

Ref. 807

Hip











Ref. CRP05



Ref. CR104





Ref. CR108

Find all the latest technical data on our website, www.edilians.co.uk