COLOURS

To overcome any minor shade variations inherent in the production of natural clay products, we recommend that tiles are mixed from





BURNT RED





BROWN

SLATE



VALLÉE DE CHEVREUSE

The colours shown here are only as accurate as allowed for by the printing process. Product samples are available on request.







This product was manufactured by an organisation certified compliant, by AFNOR Certification, with the following benchmarks: ISO 9001 for quality, ISO 14001 for the environment, and ISO 50001 for energy. All EDILIANS roof tiles comply with the requirements of the NF EN 1304 standard. Only tile models identified by the NF, NFM, or NFFP logo are compliant with the requirements of the NF063 Clay Roof Tiles certification. The characteristics certified by the NF Clay Roof Tiles specification are appearance, geometric characteristics, resistance to breakage by bending, Class I waterproofing, resistance to freezing in accordance with NF EN 539-2, resistance to "mountain climate" freezing (for models bearing the NFM logo only), and suitability for use on low-pitch roofing (for models bearing the NF FP logo only). www.marque-nf.com

HP 17 Huguenot

CLAY TILE

Small Format Flat Interlocking Tile

Ref. 325



HP 17 Huguenot

Small Format Flat Interlocking Tile

Technical data

Quantity per pallet: 420 tiles

Coverage at 285mm gauge:

17.2 tiles per m²

Batten gauge (variable)*:

222mm minimum 285mm maximum

Overall length:

358mm

Overall width: 246mm

Cover width: 204mm

Minimum headlap:

Weight per tile: 2.6kg

Weight per m² at maximum gauge:

44.7kg

Minimum roof pitch: 20.0°

Batten coverage m² at 285mm gauge:

3.51m

Batten sizes:

38 x 25mm for rafter centres up to 450mm

50 x 25mm for rafter centres up to 600mm

Tile nail:

50 x 3.35mm aluminium clout head

* Always check each batch of tiles delivered to site to determine the actual gauge, which may vary slightly due to drying and fi ring shrinkage during the manufacturing process

PRODUCT ADVANTAGES FOR ARCHITECTS

CLAY TILE

Small Format Flat Interlocking Tile

The HP17 is a small format interlocking clay tile with an attractive tapered leading edge and is designed to be installed quickly and efficiently due to its adjustable batten gauge from 222mm to 285mm and double hole facility.

A large range of accessories complement its modern appeal, offering excellent dry fix options at ridge, hips and verges ensuring a long-term maintenance-free durable roof, supported by our comprehensive insurance backed durability guarantee. The HP17 has a smooth surface finish in a variety of permanent colours, one of the undeniable qualities of natural fired clay.

FEATURES

This small format interlocking tile, which is both elegant and economical, is popular because of its technical characteristics, offering an attractive solution both in terms of cost and ease of installation, thanks to its variable gauge.

The modern design of the HP17 offers high durability and technically superior performance even in the most severe weather conditions, providing an economical solution for restoration or new-build projects. Available in five distinct colours to adorn the roofs of your region.

ACCESSORIES AND FITTINGS

An extensive range of accessories covering all roofing needs

Verge




Ref. 325.01





Ref. 325.84

Cloaked verge



Ref. 325.71

Ref. 325.70


Half tile Ref. 325.01 is required with HP17 cloaked verge tiles to break the bond

Angular ridge




Ref 710





716 Ornamental ridge



ridge (2.5 per m) Ref 716





Ref 809

Half round interlocking ridge







end piece, socketer Ref 807

Half round non-interlocking ridge



Gothic hip





Gothic hip foot Ref. 863





Tile clip

Ref. CRV04

Clips



Eaves clip

Ref. CRP05



Verge clip



Ref. CR103



(with wire fixing) Ref. CR108

Ref. CRP717